

Stripping, Sanding, Resurfacing & Polishing

The GP17B is built for high productivity in the harshest jobs like concrete resurfacing, natural stone polishing, and wood screening and sanding. Designed with the powerful 1.5 HP 180 frame TEFC (Totally Enclosed Fan Cooled) AC motor and gearbox fit with 11:1 hardened helical cut gears and an industrial grade steel coupler. This combination of motor and gears weighs 30 pounds more than a standard machine of similar size.

The machine is built with the 360 dust pickup system, using a 16 gauge steel, powder-coated brush cover with a 360 degree dust collecting duct and 2" dust exhaust port. All commercial tank vacuums with a 1.5" or 2" hose connect to this port. Remove the heaviest soils by adding the optional 50 lb. weight set with transport lock.

Power and Drive System:

- 180 frame TEFC dual capacitor AC motor
- 115-230V, 60 Hz power. (50 Hz optional).
- 50 ft., 2-pc. 12-3 SJTOW industrial power cord with twist lock molded plug
- Extra heavy duty gear box, with XHD steel helical-cut 11:1 gears and steel coupler

Engineered Design:

- Proprietary 360 brush cover with wrap-around dust guard to pick up dusts and debris
- Extra heavy duty steel handle with incorporated hose support
- Comfortable vinyl-dipped foam hand grips
- Heavy duty motor guard protects the motor from impact damage
- Dual steel operating triggers with negative pressure on/off switch
- Thumb-operated safety switch. Comfortable vinyl-dipped foam grips.
- 2" x 6" non-marking load bearing, ball bearing wheels
- Optional (2) 25 lb. removable weight set, with locking pins and transport lock (See accessories next page)

Safety Features:

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



Shown with
an Optional
Weight Set



Specifications

Model	GP17B
Part #	F-GP17B
Machine Size	17 inch
Pad Size	16 inch
Pad Speed	165 RPM
Amp Draw	7.9 Amp
Machine Wt.	133 lbs.
Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power	115-230V, 60 Hz power (50 Hz optional)
Power Cord	50 ft. 12-3 SJTOW industrial power cord w/molded plug
Drive System	Triple-planetary XHD 11:1 helical-cut industrial gears
dB Rating	66 dB - Meets GS42 standard



The Handle-Mounted
Hose Support Carries
1.5" and 2" Vacuum Hoses



Variable Handle Height
Adjustment and
Transport Lock



The Steel Brush Cover
is Built with a 1.5" or
2" Vacuum Port



360° Duct in the Brush
Apron Directs Debris to
the 2" Vacuum Port


Accessories



Transport Lock Kit
with Variable
Handle Height
Adjustment
#HP0005



Brute 360 Weights
(2) 25# Optional
Weights with
Locking Pins
#A360-17 -17"



**Premium Sandpaper
Driver**
Plywood Block, Cushion
Pad, 1" Riser
#A0014-HD - 17"



**Economy Sandpaper
Driver**
Molded Plastic Block,
Cushion Pad, 1" Riser
#A0014 - 17"



**Weighted Diamond
Pad Driver**
Steel Block & Aluminum
Clutch Plate
#A0010WTDPD - 17" (46#)



**Claw Diamond Disc
Driver**
#CLAW17 - 17"



**HAWK Surface Prep
Scraper**
With replaceable
carbide blades
#HP0033 - 17"



Orbitec Diamond Driver
(6) Cups Hold 3"
Diamond Tools,
Aluminum Clutch Plate
#HP0017-3 - 17"




Poly Scrub Brush
For general scrubbing
#A0002- 17"
#A0003 - 20"



Nylon Carpet Brush
Scrub with soft & stiff
nylon bristle mix
#A0006-17"
#A0007- 20"



Black 80 Grit Brush
Strip/scrub with stiff
black 80 Grit bristles
#A0008 - 17"



**Tufted Pad Driver
w/ Riser**
Molded Plastic Block,
1" Riser
#A0010-4 - 17"